

## Satellite set

### CLICKFAST



#### Electrical and Mecanical characteristics

Frequencies (GHz)	10,7 - 12,75
Dish dimension (mm)	708 X 653
Efficiency (%)	> 74
Gain @ 10.7-12.75 GHz (dB)	36 @ 37,50
Polarisation discrimination (dB)	22
Secondary lobe discrimination (dB)	> 27
Noise temperature @ 30° elevation (K)	46
F/D ratio	0,65
Opening angle @ - 3 dB (deg)	> 2,7
Operational elevation (deg)	7 - 87
Pointing offset angle (deg)	22
Mast diameter (mm)	30 - 90
Survival windloading (km/h)	40 m/s > 144
Operational temperature range	- 30° C / + 70° C
Source diameter (mm)	40
Pre-mounting of the steel mount	Yes
Disc material and bracon	Aluminum
Dish colors avaivable	Standart Anthracite Tuile
Section of the aluminium bracon (mm)	20 X 50

#### Product advantages ...

- Ultra fast assembly
- Galvanised steel mount
- Pre-mounted Bracon (1)
- Pre-mounted LNB bracket (2)
- Crimped nuts on mount
- 13 mm hexagon nuts

#### Composition of the set ...

- 1 CLICKFAST dish
- 1 LNB UST100
- 1 double fluted box

#### logistics info ...

- Reference : Clickfast
- Packaging : 1 set = 1 box
- 1 pallet = 40 sets



(1) pre-mounted on the mount  
(2) pre-mounted on the bracon

Hot Line **0 899 707 205** Service 0,80 € / min  
+ prix appel

[www.servimat.fr](http://www.servimat.fr)